



## MD78X/78XG

Versatile Digital Mobile Two-Way Radio

- Large-size HD Transflective Color Display
- Superior Digital Voice







## MD78X/78XG

Higher Efficiency,  
Richer Experience



As a product built to the DMR standard, MD78X/78XG (MD78XG is the model with GPS) is endowed with ergonomic design, all-round digital functions and remarkable quality to increase your management efficiency and enable you to be responsive to emergent situations.

## Applications

Public Safety  
Forest Industry

Public Utilities  
Business

Transportation (port, airport, railway, etc.)  
Manufacturing



## Product Features

### ● User-centered Design

The large-size color display allows good visibility even under extremely strong light. And the seven programmable keys facilitate your communication in various conditions.

### ● Reliable Quality

MD78X/78XG is strictly compliant with MIL-STD-810 C/D/E/F/G and IP54 standards, ensuring outstanding performance even under harsh environments.

### ● Superior Voice

With the combined application of narrowband codec and digital error-correction technologies, MD78X/78XG is capable of ensuring you superior voice under noisy environments or at the edge of the coverage area. In addition, the adoption of the AGC technology also optimizes your voice. With a built-in 4W speaker, MD78X/78XG ensures clear and crisp voice communication.

### ● Higher Spectrum Efficiency, Higher Channel Capacity

Benefiting from the TDMA technology, MD78X/78XG allows twice the channels based on the same spectrum resource. This is a big help to relieve the stress of increasing shortage in spectrum resource.

### ● Dual-slot Pseudo Trunk

With this feature, the free slot can be allocated to a member that needs to communicate, effectively enhancing frequency efficiency and allowing you to communicate timely under emergency situations.

### ● Secure Communication

Besides the intrinsic encryption of the digital technology, MD78X/78XG provides enhanced encryption capability (such as 256-bit encryption algorithm) and the Scrambler feature (selectable).

### ● Versatile Services

In addition to conventional communication services, MD78X/78XG features rich data services and selectable functions such as Text Message, Scan, Emergency, Channel Steering, Auto Registration and Lone Worker.

### ● Further Development Port

The reserved front and rear port in MD78X/78XG allows users or any third party partner to further develop other helpful applications to extend the radio functionalities!

### ● Option Board Interface

MD78X/78XG supports option board interfaces to radio, allowing third party partner to develop various applications to interconnect with radios to control the radio to expand its functionalities! Among the supported features are voice recording, encryption etc. Please refer to the API Partner Programmed for more information!

## Main Functions

### ● Dual Modes (Analog+Digital)

MD78X/78XG can operate in either analog or digital mode. It is compatible with the prevalent analog system, ensuring a smooth analog-to-digital transition.

### ● Versatile Voice Calls

Intelligent signaling of MD78X/78XG supports various voice call types, including Private Call, Group Call, All Call and Emergency Call.

### ● GPS

MD78XG supports viewing of GPS positioning information and sending of GPS text message.

### ● Data Services

MD78X/78XG supports data capabilities of sending Private, Group text message. It also supports Third Party to control the radio via Third party API (GPS, Radio Registration Services, Radio Call Control, Telemetry, Data Transfer), via Telemetry control to radio.

### ● Accessory Expansion

MD78X/78XG supports third party to develop accessories expansion via front and rear port of the mobile. (Check out that features as channel steering, emergency footswitch has been supported via the back port!)

### ● Various Analog Signaling Types

MD78X/78XG supports various analog signaling types (HDC1200, DTMF phone, 2-Tone and 5-Tone), various squelch control types (CTCSS/CDCSS), thus providing higher function expansion capacity to the analog world.

### ● Supplementary Services

MD78X/78XG supports supplementary services of Radio Check, Remote Monitor, Call Alert, Radio Enable and Radio Disable.

### ● Multiple Languages

MD78X/78XG supports up to 15 languages, including English, Simplified Chinese, Traditional Chinese, Thai, Arabic, Farsi, Korean, Portuguese, Italian, Russian, Polish, Turkish, French, Spanish and German, allowing users to select it per their needs.

### ● One Touch

MD78X/78XG supports One Touch features that comprise of Text Message, Voice Calls and Supplementary Services.

### ● Scan

MD78X/78XG supports scanning of pure analog voice and signaling, pure Digital voice and data, and also mix mode scan that comprise of Analog and Digital activities.

### ● Roaming

MD78X/78XG supports automatic roaming of all sites in a IP Multi-site Connect system.

### ● Privacy of Voice and Data

MD78X/78XG supports analog scrambling, and digital encryption using Advanced Encryption Standard (AES) and ARCFOUR (ARC4) encryption methodology to both voice and data.

### ● Analog/Digital Telephone Interconnect (via DTMF signaling)

MD78X/78XG supports simplex voice communications between radio and telephone users. It allows a radio user to make a telephone call; or a telephone user to make either a Group or Private call to radio users. This feature utilizes the Commercial Off The Shelf (COTS) Analog Phone Patch boxes and a Plain Old Telephone Service (POTS) line to connect the radio users to the Corporate Office Phone System (PBX) or Public Switched Telephone Network (PSTN).

### ● Software Upgradable

Upgrade software enables new features without buying a new radio; MD78X(G) could also be switched into MPT and DMR trunking modes with corresponding trunking license applied in the same hardware.

## Standard Accessories

Palm Microphone  
Power Cord

Microphone Hanger  
Fuse

Microphone Hanger Screws  
GPS Antenna ( for MD78XG only )

Mounting Bracket



# Specifications

General	Frequency Range	UHF1: 400-470MHz; UHF2: 450-520MHz UHF3: 350-400MHz; UHF5: 804-941MHz* VHF: 136-174MHz		
	Channel Capacity	1024		
	Zone Capacity	64(each with a maximum of 16 channels)		
	Channel Spacing	12.5 KHz / 20 KHz / 25 KHz		
	Operating Voltage	13.6 V ± 15%		
	Current Drain	Standby	< 0.6A	
		Receive	< 2.0A	
			5W	< 5A
		Transmit	25W	< 8A
	45W/50W		< 12A	
Frequency Stability	± 1.5ppm			
Antenna Impedance	50			
Dimensions (H x W x D)	60 x 174 x 200 mm			
Weight	1.7Kg			
LCD Display	220 x 176 pixels, 262000 colors, 2.0 inch, 4 rows			
Receiver	Sensitivity	Analog	0.3 μ V (12dB SINAD); 0.22 μ V (Typical) (12dB SINAD) 0.4 μ V (20dB SINAD)	
		Digital	0.3 μ V / BERS5%	
	Selectivity TIA-603 ETSI	65dB @ 12.5KHz / 75dB @ 20/25KHz <sup>#</sup> 60dB @ 12.5KHz / 70dB @ 20/25KHz <sup>#</sup>		
		Intermodulation TIA-603 ETSI	75dB @ 12.5/20/25KHz <sup>#</sup> 70dB @ 12.5/20/25KHz <sup>#</sup>	
	Spurious Response Rejection TIA-603 ETSI		75dB @ 12.5/20/25KHz <sup>#</sup> 70dB @ 12.5/20/25KHz <sup>#</sup>	
		Blocking TIA-603 ETSI	90dB 84dB	
	Hum and Noise		40dB @ 12.5KHz; 43dB @ 20KHz; 45dB @ 25KHz <sup>#</sup>	
		Rated Audio Power Output	Internal (@20 ohm load)	3W
	External (@8 ohm load)		7.5W	
	Max Audio Power Output	Internal (@20 ohm load)	8W	
External (@8 ohm load)		20W		
Rated Audio Distortion	3%			
Audio Response	+1 ~ -3dB			
Conducted Spurious Emission	< -57dBm			

Transmitter	RF Power Output	Low Power UHF1/UHF2/UHF3: 5-25W VHF: 5-25W
		High Power UHF1/UHF2/UHF3: 5-45W; UHF5*: 5-35W VHF: 5-50W
	FM Modulation	11K0F3E @ 12.5KHz; 14K0F3E @ 20KHz 16K0F3E @ 25KHz <sup>#</sup>
	4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW
	Conducted/Radiated Emission	-36dBm<1GHz; -30dBm>1GHz
	Modulation Limiting	± 2.5KHz @ 12.5KHz; ± 4.0KHz @ 20KHz; ± 5.0KHz @ 25KHz <sup>#</sup>
	FM Hum & Noise	40dB @ 12.5KHz; 43dB @ 20KHz; 45dB @ 25KHz <sup>#</sup>
	Adjacent Channel Power	60dB @ 12.5KHz; 70dB @ 20/25KHz <sup>#</sup>
	Audio Response	+1 ~ -3dB
	Audio Distortion	3%
Digital Vocoder Type	AMBE++or SELP	
Digital Protocol	ETSI-TS102 361-1,-2,-3	
Environmental Specifications	Operating Temperature	-30 ~ +60
	Storage Temperature	-40 ~ +85
	ESD	IEC 61000-4-2 ( level 4 ) ± 8kV (contact) ± 15kV (air)
	American Military Standard	MIL-STD-810 C/D/E/F/G
	Dust & Water Intrusion	IP54 Standard
	Humidity	Per MIL-STD-810 C/D/E/F/G Standard
	Shock & Vibration	Per MIL-STD-810 C/D/E/F/G Standard

GPS (for MD78XK only)	Accuracy specs are for long-term tracking(95th percentile values>5 satellites visible at a nominal -130dBm signal strength)	
	TTF (Time To First Fix) Cold Start	<1 minute
	TTF (Time To First Fix) Hot Start	<10 seconds
	Horizontal Accuracy	<10 meters

\* This frequency band is only available for DMR trunking mode  
<sup>#</sup> 20KHz/25KHz will not be available on new equipment in the U.S. after 2011-01-01.  
 All Specifications are tested according to applicable standards, and subject to change without notice due to continuous development.

# Optional Accessories



**Hytera** Respond & Achieve

**Hytera Communications Corporation Limited**

Address: Hytera Tower, Hi-Tech Industrial Park North, Beihuan Rd., Nanshan District, Shenzhen, China

Tel: +86-755-2697 2999 Fax: +86-755-8613 7139 Post: 518057

Http: //www.hytera.com Stock Code: 002583.SZ

Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Communications Co., Ltd.

© 2014 Hytera Communications Co., Ltd. All Rights Reserved.